


HW Getting Started Guide

PQ-MDS-PIB

January 2006: Rev. 0.4

Step 1: Check kit contents	
<ol style="list-style-type: none"> 1. PQ- MDS- PIB (Platform I/O Board, or "PIB") 2. Power cable extension with on-off switch 3. 25 Pin IEEE 1284 Parallel cable 4. Serial cable 10cm D25M to IDC10 5. Parallel cable 10cm D25M to IDC26F 6. RJ45 to IDC8F Cable (2 pcs) 7. LC Loop back 62.5/125Fiber (2 pcs) 8. USB Cable StndA Plug to MiniB 1Meter 9. USB Cable MiniA Plug to StndB 1.5Meter 10. PMC Board assembly spacers 11. AC/DC Power Supply 48V/2.7A (Input 120-230VAC) 12. PQ- MDS- PIB Getting started guide 13. PQ- MDS- PIB Board Errata 14. PQ- MDS- PIB Documentation CD 	

The steps on the following pages describe how to connect various peripheral devices to the PIB, and how to configure the PIB to work with them. Each device is sold separately. Instructions for working with them are found in their user documentation.

Processor Board (required): [Step 2, on page 2](#)



Configure PIB to work with the agent modules you are using: [Step 3 on page 5](#)

PMC-PCI Adaptors (optional: for using up to two agents): [Step 4 on page 6](#)


Expansion Adaptor (optional: for using up to four agents): [Step 5, on page 9](#)

USB Module (optional): [Step 6, on page 12](#)

Quad-OC3 Module (optional): [Step 7, on page 13](#)


<p>Step 2: Attach Processor Board to PIB (MPC83xx processor board is sold separately)</p> <p>Step 2.a: Remove protective covers from the 300-pin connectors on the bottom side of the Processor board</p>	
<p>Step 2.b: Remove protective covers from the 300-pin connectors on the PIB.</p>	
<p>Step 2.c: Connect Processor board to PIB board as shown.</p> <p>Ensure a tight fit by pressing down on the Processor board <i>by hand only</i> until the pins engage</p>	

Step 2.d: Manually fasten the four screws as shown.




Step 2.e: If you wish GETH signals to traverse either a back plane connection, or a front plane optical connection, connect the two GETH sockets on the Processor board with sockets on the PIB board as shown.


Note that if you do not do this, you can still connect GETH cables directly to the Processor board's sockets, if they are accessible in your application's configuration.





The figure at right shows one of the GETH interconnecting cables connected to the GETH socket on the Processor board, and its counterpart on the PIB.




Step 2.f: If you are working with the PIB in a “table-top” configuration, connect the power supply to the voltage input as shown.



<p>Step 3: Use host chip on processor board to configure PIB according to your developmental needs</p> <p>If you will be working with agent modules, you must configure the PIB to accomodate these modules before these can be attached (see table at right). Once this is done, then install either the PMC-PCI adaptors (if using up to two agents) in Step 4 on page 6, or the Expansion Adaptor (if using up to four agents) in Step 5 on page 9.</p>	<p>Configure the I/O Expanders (communication devices on the PIB) via the I2C block on the MPC83xx chip. For a more detailed explanation of the I/O Expanders, see the PIB User's Manual.</p> <p>The table below shows each communication option available: which PMC slot is used (for PMC-PCI adaptors), whether the Expansion Adaptor is used, which bus is used (PCI1, PCI2) and its size (32 vs. 64 bits). Note that there are values that must always be set.</p> <p>The values must be written, via the I2C, to a register on the I/O Expander device. For example, to connect an agent board to the PMC1 slot, using the PCI1 bus at 32 bits, write the value 0xFFFF to the I2C address 0x26, register 2.</p> <p>It is important to note that the values indicated in the first five lines of the table must always be written.</p> <table border="1"> <thead> <tr> <th>Communication Option</th><th>I2C Addr</th><th>Reg #</th><th>Value</th></tr> </thead> <tbody> <tr> <td>Always set:</td><td>0x23</td><td>6</td><td>0</td></tr> <tr> <td>Always set:</td><td>0x26</td><td>6</td><td>0x0034</td></tr> <tr> <td>Always set:</td><td>0x27</td><td>6</td><td>0</td></tr> <tr> <td>Always set:</td><td>0x23</td><td>2</td><td>0xFFFF</td></tr> <tr> <td>Always set:</td><td>0x27</td><td>2</td><td>0xFFEF</td></tr> <tr> <td>PCI1 - Expansion Adaptor 64 bit</td><td>0x26</td><td>2</td><td>0xFCFF</td></tr> <tr> <td>PCI1 - Expansion Adaptor 32 bit</td><td>0x26</td><td>2</td><td>0xF8FF</td></tr> <tr> <td>PCI1 - 64bit on PMC2¹</td><td>0x26</td><td>2</td><td>0xF4FF</td></tr> <tr> <td>PCI1 - PMC1 32bit</td><td>0x26</td><td>2</td><td>0xFFFF</td></tr> <tr> <td>PCI1 - PMC1 & PMC2 32bit</td><td>0x26</td><td>2</td><td>0xF7FF</td></tr> <tr> <td>PCI1 - PMC1, PMC2 & PMC3 32bit</td><td>0x26</td><td>2</td><td>0xF3FF</td></tr> <tr> <td>PCI1 - PMC1 & PMC2 32bit PCI2 - PMC3 32bit</td><td>0x26</td><td>2</td><td>0xF5FF</td></tr> <tr> <td>PCI2 - PMC3 32bit</td><td>0x26</td><td>2</td><td>0xFDFF</td></tr> <tr> <td>PCI2 - PMC2 & PMC3 32bit</td><td>0x26</td><td>2</td><td>0xF9FF</td></tr> </tbody> </table> <p>¹ If PCI1 can be 64 bits in size. This depends on the specific MPC83xx host model. Refer to its User's Manual for specifications.</p>	Communication Option	I2C Addr	Reg #	Value	Always set:	0x23	6	0	Always set:	0x26	6	0x0034	Always set:	0x27	6	0	Always set:	0x23	2	0xFFFF	Always set:	0x27	2	0xFFEF	PCI1 - Expansion Adaptor 64 bit	0x26	2	0xFCFF	PCI1 - Expansion Adaptor 32 bit	0x26	2	0xF8FF	PCI1 - 64bit on PMC2 ¹	0x26	2	0xF4FF	PCI1 - PMC1 32bit	0x26	2	0xFFFF	PCI1 - PMC1 & PMC2 32bit	0x26	2	0xF7FF	PCI1 - PMC1, PMC2 & PMC3 32bit	0x26	2	0xF3FF	PCI1 - PMC1 & PMC2 32bit PCI2 - PMC3 32bit	0x26	2	0xF5FF	PCI2 - PMC3 32bit	0x26	2	0xFDFF	PCI2 - PMC2 & PMC3 32bit	0x26	2	0xF9FF
Communication Option	I2C Addr	Reg #	Value																																																										
Always set:	0x23	6	0																																																										
Always set:	0x26	6	0x0034																																																										
Always set:	0x27	6	0																																																										
Always set:	0x23	2	0xFFFF																																																										
Always set:	0x27	2	0xFFEF																																																										
PCI1 - Expansion Adaptor 64 bit	0x26	2	0xFCFF																																																										
PCI1 - Expansion Adaptor 32 bit	0x26	2	0xF8FF																																																										
PCI1 - 64bit on PMC2 ¹	0x26	2	0xF4FF																																																										
PCI1 - PMC1 32bit	0x26	2	0xFFFF																																																										
PCI1 - PMC1 & PMC2 32bit	0x26	2	0xF7FF																																																										
PCI1 - PMC1, PMC2 & PMC3 32bit	0x26	2	0xF3FF																																																										
PCI1 - PMC1 & PMC2 32bit PCI2 - PMC3 32bit	0x26	2	0xF5FF																																																										
PCI2 - PMC3 32bit	0x26	2	0xFDFF																																																										
PCI2 - PMC2 & PMC3 32bit	0x26	2	0xF9FF																																																										

<p>Step 4: Attach PMC-PCI (PQ-MDS-PMCPPI) adaptors to PIB</p> <p>(PMC-PCI adaptors are sold separately)</p> <ul style="list-style-type: none"> • Each PMC-PCI adaptor can accommodate one PCI board as an agent. • To work with up to two PCI-format boards as agents at the same time (on two different PCI buses), use PMC-PCI modules to attach them to the PIB • To work with more than two agents, use the expansion adaptor, shown in Step 5 on page 9. • For the exact possible configurations and combinations of agent locations (not all slots can be used for every situation), bus name(s), host and agent modules, see the PIB User's Manual or the relevant Processor Board's User's Manual. 	 <p>PMC-PCI adaptor (view from above) PMC-PCI adaptor (view from below)</p>
<p>Step 4.a: Connect each PMC-PCI adaptor as shown, and press in firmly (by hand) until it clicks in place.</p> <p>The PMC-PCI adaptors can be inserted into the PMC1, PMC2, or PMC3 slots.</p> <p>The PMC0 slot is reserved for non-PCI modules.</p>	 <p>Connect as shown Tighten by hand</p>

Step 4.b: Insert spacers between the PMC-PCI adaptors and the PIB, and tighten them using a screwdriver.




The figure at right shows a close-up view of a PMC-PCI adaptor installed on the PIB.




The figure at right shows three PMC-PCI adaptors installed on the PIB.

A processor board and a USB module are also shown installed on the PIB.



Step 4.c: Insert a PCI-compatible board as an agent into the slot on the PMC-PCI adaptor.



Step 5: If you wish to use more than two agents, attach the expansion adaptor

(PQ-MDS-PCIEXP) to the PIB.
(the expansion adaptor, including the riser cards and its own dedicated power supply, is sold separately)


- The expansion adaptor is used **instead** of the PMC-PCI modules if more than two agent modules are needed.
- The expansion adaptor can accommodate **up to four** PCI boards (working at the same time, on the same bus) as agents.
- For the exact possible configurations and combinations of agent locations (not all slots can be used for every situation), bus name(s), host and agent modules, see the PIB User's Manual or the relevant Processor Board's User's Manual.

Step 5.a: If using a module in the PMC0 slot, insert riser cards on PIB

These riser cards are used to raise the expansion adaptor to the proper height when a module is installed in the PMC0 slot (the figures show this slot with no module installed).

Insert the three riser cards as shown, starting from the PMC3 slot, and continuing to the PMC1 slot.

Press each riser card firmly in until it clicks in place.




Step 5.b: Connect expansion adaptor to PIB


Connect the expansion adaptor (PQ-MDS-PCIEXP) to the PIB as shown. If no module is used in the PMC0 slot, the riser cards are not needed, as shown in the figure.



If a module (such as a USB module or a QOC3 module) is installed in the PMC0 slot, the riser cards must be used (refer to [Step 5.a on page 9](#) for instructions).

Press the PQ-MDS-PCIEXP in firmly until it clicks in place.




The figure at right shows an expansion adaptor installed on the PIB.



<p>Step 5.c: Connect power supply to the expansion adaptor (PQ-MDS-PCIEXP).</p> <p>Use the 20-pin connector only.</p> <p>This is a dedicated power supply, included in the expansion adaptor kit.</p> <p>(Note that the PIB must also be connected to its own power supply. See Step 2.f on page 4)</p>	
<p>Step 5.d: Insert a PCI-format module(s) as an agent on the expansion adaptor as shown (MPC83xx board shown).</p> <p>Up to four agent modules can be inserted at any one given time.</p>	

Step 6: If working with the USB module, attach it to the PIB and press in firmly (by hand) until it clicks in place. (USB module is sold separately)

USB module can only be used in slot PMC0.



Step 7: If working with the QOC3 module


(PQ-MDS-QOC3), attach it to the PIB and press in firmly (by hand) until it clicks in place. (QOC3 module is sold separately)

The QOC3 can be connected to the PMC0 and/or the PMC1 slot on the PIB.

Use the metal spacers (provided in the QOC3 kit) to hold the QOC3 Module in position on the PIB. The metal spacers are optional, and can be removed if necessary.




Position QOC3 Module above PMC slot



Press down until module snaps in place

The figure at right shows a QOC3 module installed on the PIB.



How to Reach Us:**USA/Europe/Locations Not Listed:**

Freescale Semiconductor Literature Distribution Center
P.O. Box 5405
Denver, Colorado 80217
1-800-521-6274 or 480-768-2130

Japan:

Freescale Semiconductor Japan Ltd.
Technical Information Center
3-20-1, Minami-Azabu, Minato-ku
Tokyo 106-8573, Japan
81-3-3440-3569

Asia/Pacific:

Freescale Semiconductor Hong Kong Ltd.
2 Dai King Street
Tai Po Industrial Estate
Tai Po, N.T., Hong Kong
852-26668334

Home Page:

www.freescale.com

Information in this document is provided solely to enable system and software implementers to use Freescale Semiconductor products. There are no express or implied copyright licenses granted hereunder to design or fabricate any integrated circuits or integrated circuits based on the information in this document.

Freescale Semiconductor reserves the right to make changes without further notice to any products herein. Freescale Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Freescale Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters that may be provided in Freescale Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals", must be validated for each customer application by customer's technical experts. Freescale Semiconductor does not convey any license under its patent rights nor the rights of others. Freescale Semiconductor products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Freescale Semiconductor product could create a situation where personal injury or death may occur. Should Buyer purchase or use Freescale Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold Freescale Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Freescale Semiconductor was negligent regarding the design or manufacture of the part.

Learn More: For more information about Freescale products, please visit www.freescale.com.

Freescale™ and the Freescale logo are trademarks of Freescale Semiconductor, Inc. All other product or service names are the property of their respective owners.

© Freescale Semiconductor, Inc. 2006. All rights reserved.